



ELECTRONIC WATER PRESSURE SYSTEM



We conceived e.sybox according to our idea of ergonomic technology* and we have developed it enclosing and expressing all the DAB technological know-how based on 37 years of experience in the mechanics and electronics sector.

EJUDOX

A new **PATENTED** milestone of DAB evolution.

The result is a system, the only one of its kind, efficient, compact, easy to use and satisfactory for the installer as well as the final user.

Thanks to these features, the e.sybox is the most evolved ergonomic system in the world in the field of water pressurization for domestic and residential use.

PRODUCT EVOLUTION



ACTIVE EI

-

SMART PRESS

JET







AQUAJET





ERGONOMIC TECHNOLOGY





*Ergonomic technology is characterised by a high level of usability, which may be expressed by means of the following dimensions: • the ease of installation

- the ease of learning to operate the system
- a satisfactory use

see more about ديناهم www.dabpumps.com/e.sybox







e.rybox



20

н

70

kPa 700 m

600 60

500 50

400 40

300 30

200 20

100 10 25

20

Q US gpm

Q IMP gpm

ft

-36

-32

-24

16

30

25





All this is enclosed inside a "case" with its typical Italian design.







INVERTER ELECTRONIC BOARD

Thanks to the Inverter technology, e.sybox draws the energy necessary according to the water requirements, thereby avoiding futile wastes and allowing considerable economic savings.



SENSORS

The new compact electronic pressure transducer with built-in temperature sensor developed by DAB, together with the flow sensor, both positioned on the pump delivery, send the necessary signals to the board for proper control of the system.



INTERNAL HYDRAULIC CONNECTIONS

Designed to minimise the dimensions, ensure compactness of the system and make maintenance easy.



EXPANSION TANK

Integrated in the system, it has a 2-litre capacity and is certified for drinking water. Comes with a 5-year guarantee, no maintenance required.



EFFICIENT AND INTEGRATED



2013



see more about دیں۔ www.dabpumps.com/e.sybox





VERTICAL INSTALLATION

The features and design of the e.sybox make the system easily adaptable to any type of installation.

Horizontal or Vertical, in a ventilated room or in a recess, any setting will be perfect for making the best possible use of the e.sybox, which ensures a reduction of at least 30% of the dimensions as compared to any other traditional system.



HORIZONTAL INSTALLATION

263L x 352P x 564H*



*e.sybox vertical



EXTERNAL CONNECTIONS

Covered with caps fitted with gasket. Easy to remove, the suction and delivery of the system to be used can be easily selected, depending on the installation.



DISPLAY

LCD 70x40 mm high-resolution adjustable for easy reading in the various installations. The user-friendly interface makes it possible to access all the information and customise the main settings according to the specificity of the application.



TECHNICAL COMPARTMENT

Allows easy access to the rotor shaft, vertical filling plug and expansion tank. It is also a practical housing for the maintenance tools and user's guide, functional for using the system.



COMPACT AND VERSATILE







MOTOR

New water-cooled motor highly resistant to corrosion. Makes it possible to install the system in a recess.



CHECK VALVE AT THE DELIVERY

Allows horizontal as well as vertical installation of the system. It can be easily removed to facilitate maintenance



PROTECTION OF THE WATER IN THE SYSTEM FROM FREE-ZING (ANTI FREEZE)

e.sybox is provided with a protection device which prevents the formation of ice inside, by activating the pump in case the temperature falls below values approaching freezing point.

e.rybox

Every detail of the e.sybox is carefully designed to ensure the levels of comfort which fix new reference standards for the sector.

Just connect the e.sybox to the power socket to have all the water required, when it is required.

The noise perceived as well the vibrations are reduced to the minimum and the system is whisper-silent only 45 dB in standard use.





HYDRAULICS Multi-stage self-priming up to 8 m.



MOTOR

The new water-cooled motor eliminates noise generated by the traditional cooling fans.



INVERTER

The new variable-speed electronics ensures constant pressure in relation to the flow rate. The systems with inverter technology make less noise compared to the traditional on/off systems because they regulate the motor rpm according to requirements and are also equipped with gradual startup and switch off.



SILENT AND COMFORTABLE







ENCLOSURES

Made of ABS material, enclose the system, with protective and sound-proofing function.



ANTIVIBRATION FEET

Ensure effective absorption of vibrations, making the e.sybox even more silent and comfortable. They are designed for horizontal and vertical installation of the system

> see more about ديناهم www.dabpumps.com/e.sybox





With e.sybox the accessories become real functional components, ergonomic extensions of the product.

e.sydock, e.sytwin and e.sywall were developed to provide a new experience in the installation and use.





1" ¼ SUCTION AND DELIVERY FITTINGS

293L x 318P x 180H*





Kit complete with brackets, screws, dowels and two accessories for absorption of vibrations.



293L x 345P x 679H*

e.rydock

e.sydock, thanks to the 4 plumbing configuration possibilities offers an 'installation even more rapid, easy and flexible.

e.sydock is complete with all the interfaces required for connecting to the system.

Also the maintenance has never been so simple thanks to the rapid disconnect function.

e.sydock incorporates anti vibration feet to ensure the same quietness as e.sybox.



ERGONOMIC EVOLUTION





1" ¼ SUCTION AND DELIVERY FITTINGS

* e.sytwin



*with e.svbox installed

Functionality of the group viewable on every

see more about E.Jubox www.dabpumps.com/e.sybox





ϾͺʹϽʹϤͳϢͿϽ

e.sytwin is the evolution of e.sydock, of which maintains all the benefits, for the creation of two groups of pumps.

A BETTER, LONGER LIFE

e.sytwin ensures constant water supply to housing thanks to the BACKUP function.

The new software algorithms constantly analyze the operation of the system, thus optimizing the alternating use of the two units.

MORE POWER, LESS SPACE

e.sytwin offers exceptional performance thanks to possibility of combined operation with a reduced size of 50% compared to any other equivalent traditional system.

EVERYTHING YOU NEED

the wireless interface handles the communication between the two unit, e.sydock ensures the hydraulic connection and it is thanks to this technology that e.sytwin does not need any other additional components for its installation and operation.

single display.





DAB PUMPS LTD.

Unit 4 and 5, Stortford Hall Industrial Park Dunmow Road, Bishops Stortford, Herts CM23 5GZ - UK salesuk@dwtgroup.com Tel. +44 1279 652 776 Fax +44 1279 657 727

DAB PUMPS B.V.

Brusselstraat 150 B-1702 Groot-Bijgaarden - Belgium info.belgium@dwtgroup.com Tel. +32 2 4668353 Fax +32 2 4669218

PUMPS AMERICA, INC. DAB PUMPS DIVISION 3226 Benchmark Drive Ladson, SC 29456 USA info.usa@dwtgroup.com Tel. 1-843-824-6332 Toll Free 1-866-896-4DAB (4322)



000 DWT GROUP

Fax 1-843-797-3366

100 bldg. 3 Dmitrovskoe highway 127247 Moscow - Russia info.russia@dwtgroup.com Tel. +7 495 739 52 50 Fax +7 495 485-3618



DWT South Africa

Podium at Menlyn, 3rd Floor, Unit 3001b, 43 Ingersol Road, C/O Lois and Atterbury street, Menlyn, Pretoria, 0181, South-Africa info.sa@dwtgroup.com Tel +27 12 361 3997 Fax +27 12 361 3137



DAB PUMPS B.V.

Albert Einsteinweg, 4 5151 DL Drunen - Nederland info.netherlands@dwtgroup.com Tel. +31 416 387280 Fax +31 416 387299



DAB PUMPEN DEUTSCHLAND GmbH

Tackweg 11 D - 47918 Tönisvorst - Germany info.germany@dwtgroup.com Tel. +49 2151 82136-0 Fax +49 2151 82136-36



DAB PUMPS IBERICA S.L.

Parque Empresarial San Fernando Edificio Italia Planta 1ª 28830 - San Fernando De Henares - Madrid Spain info.spain@dwtgroup.com Tel. +34 91 6569545 Fax: +34 91 6569676



No.40 Kaituo Road, Qingdao Economic & Technological **Development Zone** Qingdao City, Shandong Province, China PC: 266500 info.china@dwtgroup.com Fax +8653286812210 Tel. +8653286812030-6270

